

# Professional 4 inch desktop label printers

**TD Series**

[brother.co.nz](http://brother.co.nz)





# Versatile, high-resolution desktop printers



Brother's range of TD professional label printers offer the ability to print high quality labels on demand, whatever the requirement. Printing labels up to 4 inches in width, and with direct thermal and thermal transfer print technology, they fit the requirements of a large range of vertical market applications.



TD professional  
desktop label printers



## Seamless Integration

Brother's new high specification 4 inch desktop label printers bring you improved operational efficiency with easy to use, high speed and continuous label printing. Combined with seamless integration and modular design, print from virtually anywhere in the workplace. Supporting a variety of printer command languages including ZPL II emulation allows you to integrate into existing legacy systems.



TD-4410D  
TD-4420DN  
TD-4520DN



TD-4550DNWB



TD-4420TN / TD-4520TN



# Professional label printing



**BLOOD SAMPLE  
BOTTLES**

Labels are often required to display a considerable amount of important information, so you need a printer that can put it all together efficiently, with consistent, high-quality results.

The TD Series of desktop label printers offers direct thermal and thermal transfer high speed printing, at up to 300 dpi resolution. Options include a peeler or automatic cutter, for producing continuous media to your required length on demand.

The software supports barcode printing, embellish font programming for highlighting specific words, and also allows you to import graphics and date formats for a truly personalised solution.



## Printing Technology

### Direct Thermal

Low-cost, high-volume labels can be created through this process, which uses a heat-sensitive coating and thermal print head, meaning traditional printing ribbons and ink are not required. Ideal for shorter term and less permanent labelling uses.

### Thermal Transfer

Crisp, durable printing is achieved through a process in which the ink is absorbed into the label, making it ideal for applications that require robust, harder-wearing labels.

# Healthcare, medical and laboratory



With the strict regulations on the tracking of patient specimens and other items within the healthcare industry, clear, high quality labelling is essential to maintain safety and traceability.

## Applications include:

- Appointment cards
- Admission labels
- Specimen and pathology labels
- Blood bag labels
- Laboratory labels
- Microbiology labels
- Dosage/drug bag labels





# Warehousing and logistics



Efficient warehousing operation and worker productivity are critical to the success of many companies. With the most common sizes of shipping labels available and the ability to create custom size labels there are many uses for these models in the warehouse.

## Applications include:

- Shipping labels
- Carton labels
- Location labels
- Pallet identification labels
- Quality control labels
- Compliance labels





# Retail



Easy to read labels are essential for consumers to help make informed decisions prior to a potential purchase. The high print resolution and high quality labels used in this range ensure that every output printed looks professional, offering sharp text, logos and barcodes with a high contrast to ensure faultless scanning at the checkout.

## Applications include:

- Pricing labels
- Barcode labels
- Pre-packaged food ingredients labels
- Nutrition information labels
- Shelf-edge labels
- Sale/mark-down/discount pricing labels



# TD Range

## brief summary

TD-4410D	TD-4420DN	TD-4520DN	TD-4550DNWB	TD-4420TN	TD-4520TN
<b>4 Inch</b>					

### Printing

Print technology	Direct thermal		Thermal Transfer & Direct Thermal	
Print speed	203mm/sec	152mm/sec	152mm/sec	105mm/sec
Resolution	203dpi	300dpi	203dpi	300dpi
Max print width	104.1mm	108.4mm	108mm	105.7mm
Min print length	Continuous: 6.4 mm, Peeler: 12.7 mm, Cutter: 20 mm, Tear: 27 mm		Peeler: 25.4 mm Cutter: 25.4 mm Tear: 50 mm	
Max print length	3000mm		25,400mm	11,430mm
Media sensor type	Gap (Transmissive), Bar (Reflective)			
Media sensor location	Gap (Fixed), Reflective (Adjustable)			
Tear off release mode	Standard: Continuous, Tear off Optional: Peeler, Cutter			

### Connectivity

USB	●	●	●	●	●	●
Serial	●	●	●	●	●	●
Wired LAN		●	●	●	●	●
USB Host Port				●	●	●
Bluetooth				●		
Wireless LAN				●		

### General

Dimensions (mm)	180(w) x 224(d) x 155(h)		204(w) x 280(d) x 177.5(h)	
Weight	2.08kg		2.5kg	
Control panel	3 button 3 LED		7 button 3 LED	1 button 1 LED with 3 colours
LCD			●	
Operating system support	Windows 7/8/8.1/10 Linux	Windows 7/8/8.1/10, Windows Server 2008/2008R2/2012/2012R2/2016 Linux	Windows 7/8/8.1/10, Windows Server 2008/2008R2/ 2012/2012R2/2016  OS X 10.10.x,10.11.x macOS 10.12.x, 10.13.x, 10.14.x Linux	
Supported commands	P-touch Template, ESC/P, Raster, ZPL II emulation, CPCL emulation		FBPL-EZD (EPL, ZPL, ZPL II, DPL) emulation	



# TD-4D Accessories and consumable supplies

Brother has designed and engineered a wide range of accessories to help customise the solution to meet your specific labelling requirements. Brother accessories help users equip their device to cope with the specific requirements of use.

## TD-4D Additional Options

**PA-LP-002**  
TD-4D series only  
**Label Peeler**  
TD-4410D  
TD-4420DN  
TD-4520DN  
TD-4550DNWB



**PA-CU-001**  
TD-4D series only  
**Cutter**  
TD-4410D  
TD-4420DN  
TD-4520DN  
TD-4550DNWB



**PA-HU2-001**  
TD-4D series only  
**Thermal Print Head (203dpi)**  
TD-4410D  
TD-4420DN



**PA-HU3-001**  
TD-4D series only  
**Thermal Print Head (300dpi)**  
TD-4520DN  
TD-4550DNWB



**PA-PR2-001**  
TD-4D series only  
**Platen Roller (203dpi)**  
TD-4410D  
TD-4420DN



**PA-PR3-001**  
TD-4D series only  
**Platen Roller (300dpi)**  
TD-4520DN  
TD-4550DNWB



## TD-4D Consumables

RD Rolls	Size	Quantity	Colour	Item No
Continuous label roll	102mm x 44.4m	Continuous	White	RD-S01C2
Die cut label roll	102mm x 152mm	72 labels	White	RD-S02C1
Die cut label roll	102mm x 50mm	281 labels	White	RD-S03C1
Die cut label roll	51mm x 26mm	1564 labels	White	RD-S05C1
Die cut label roll	40mm x 25mm	2000 labels	White	RD-R40NZ25
Die cut label roll	55mm x 25mm	2000 labels	White	RD-R55NZ25



# TD-4T Accessories

## and consumable supplies

### TD-4T Additional Options

#### PA-LP-003

TD-4T series only  
**Label Peeler\***

TD-4420TN  
TD-4520TN



#### PA-CU-002

TD-4T series only  
**Full & Partial Cutter\***

TD-4420TN  
TD-4520TN



#### PA-RH-001

TD-4T series only  
**External Roll Holder**

TD-4420TN  
TD-4520TN



\* Dealer option

### TD-4T Consumables

RD Rolls	Size	Quantity	Colour	Item No
Continuous label roll	102mm x 44.4m	Continuous	White	RD-S01C2
Die cut label roll	102mm x 152mm	72 labels	White	RD-S02C1
Die cut label roll	102mm x 50mm	281 labels	White	RD-S03C1
Die cut label roll	51mm x 26mm	1564 labels	White	RD-S05C1
Die cut label roll	40mm x 25mm	2000 labels	White	RD-R40NZ25
Die cut label roll	55mm x 25mm	2000 labels	White	RD-R55NZ25

TD-4T Ink Out Ribbons	Width	Length	Substrate compatibilities	Item No
Standard wax	110mm / 4.33 inch	300m	Coated/uncoated paper and tags, high gloss paper	BTT300SW
Premium wax	110mm / 4.33 inch	300m	Coated/uncoated paper and tags, high gloss paper, economy synthetics	BTT300PW
Standard wax/resin	110mm / 4.33 inch	300m	Coated/uncoated paper and tags, high gloss paper, economy synthetics	BTT300SWR
Premium wax/resin	110mm / 4.33 inch	300m	Coated/uncoated paper and tags, high gloss paper, synthetics	BTT300PWR
Standard resin	110mm / 4.33 inch	300m	Coated papers and tags, synthetics, textures	BTT300SR
Premium resin	110mm / 4.33 inch	300m	Economy and speciality synthetics	BTT300PR
Standard wax	60mm / 2.36 inch	300m	Coated/uncoated paper and tags, high gloss paper	BTT300SW60
Premium wax/resin	60mm / 2.36 inch	300m	Coated/uncoated paper and tags, high gloss paper, synthetics	BTT300PWR60
Standard resin	60mm / 2.36 inch	300m	Coated papers and tags, synthetics, textures	BTT300SR60





With label design apps for desktop PC's and mobile devices, and SDK's to integrate the TD range into your own applications, you can choose the best option for your label printing needs.

Brother provides all the necessary tools required for software developers to integrate printing into their applications. Printer drivers are available for Windows OS, and Software Development Kits can be provided to support Windows Mobile\*, Android and iOS operating systems.

## Software Support Features

### P-touch Editor

Supplied as standard, you can create your own custom labels with pixel precision by using this powerful software solution. With features such as support for over 15 barcode protocols, advanced image dithering to print high quality grayscale images, and the ability to link to data contained in Excel spreadsheets for batch printing of labels, any label design is possible.

### Crop Function

Built into the Windows driver, this function helps take away the inconvenience of using A4 sheets of labels in your standard printer. This clever feature automatically scans through the document and where a barcode is present it extracts shipping or product labels one at-a-time then prints as individual on the Brother label printer.

### Template Mode

Design the required document on your Windows PC, including logos and barcodes. Once transferred and stored in the printer's memory, the template can be recalled and any data replaced, before printing with just a few short commands.

### Mobile Deploy

Cloud-based app for mobile devices (iOS and Android™), which allows IT administrators to remotely update and configure multiple Brother mobile printers. Using Mobile Deploy, the administrator can easily upload new update packages to an online location, and then share the URLs with the users.

### Printer Commands

With support for ZPL II emulation and a variety of additional printer command languages, developers can easily integrate printing into existing legacy systems (see specification tables for further details).

### Software Development Kits (SDK's)

Brother can also supply a selection of free of charge Software Development Kits to give you an easy method of incorporating label printing directly from within your own software programs. Available from: [www.brother.co.jp/eng/dev](http://www.brother.co.jp/eng/dev)

Compatibility may vary dependent on model - check table on following page







## Software

Model No	TD-4410D	TD-4420DN	TD-4520DN	TD-4550DNWB	TD-4420TN	TD-4520TN
P-touch Editor	✓	✓	✓	✓		
Mobile Deploy App				✓		
Brother Font Manager	✓	✓	✓	✓		
Printer Settings Tool	✓	✓	✓	✓		
Bartender Ultra Lite Edition					✓	✓
Brother Printer Management Tool					✓	✓
Crop Function (Windows Driver)			✓	✓		

For further details visit : <https://support.brother.com>

# The Range in detail

TD-4410D	TD-4420DN	TD-4520DN	TD-4550DNWB	TD-4420TN	TD-4520TN
4 Inch					

## Printing

Print technology	Direct thermal			Thermal Transfer/ Direct Thermal	
Print speed	203mm/sec		152mm/sec	152mm/sec	105mm/sec
Resolution	203dpi		300dpi	203dpi	300dpi
Max. print width	104.1mm		108.4mm	108mm	105.7mm
Min. print length	Continous: 6.4mm, Peeler: 12.7mm, Cutter: 20mm, Tear: 27mm			Peeler: 25.4mm, Cutter: 25.4mm Tear: 50mm	
Max. print length	3000mm			25,400mm	11,430mm
Media sensor type	Gap (Transmissive), Bar (Reflective)				
Media sensor location	Gap (Fixed), Reflective (Adjustable)				
Tear off release mode	Standard: Continuous, Tear off Optional: Peeler, Cutter				

## Media

Media types	Wristbands, Continuous, Die cut, Fan fold, Perforated, Tag				
Media thickness	0.058mm - 0.279mm (0.002 inch to 0.011 inch)			0.06 - 0.19 mm (0.002 inch to 0.007 inch)	
Media width	19mm - 118.11 mm (0.75 inch to 4.65 inch)			20 - 112mm (0.79 inch to 4.41 inch)	
Media length	6.4mm - 3,000 mm (0.25 inch to 118.11 inch)			5mm - Max. print length (0.20 inch to Max inch)	
Diameter (Max)	127mm (5 inch)			127mm (5 inch)	
Core Diameter (Max)	12.7mm (0.5 inch)			25.4mm & 38.1mm (1.0 inch & 1.5 inch)	

## Ribbon

Types	Wax, Wax/Resin, Resin				
Wound type	Outside wound				
Ribbon width	40 - 110 mm (1.57 inch to 4.33 inch)				
Suggested paper core width	0.5 inch paper core: fixed width 110mm, width 2 notches in each side 1inch paper core: fixed width 110mm with 2 notches in each side 1inch paper core: paper core width is the same as ribbon width and use with ribbon spindles				
Inner paper core & ribbon length	0.5 inch paper core: Max. OD 40mm, 110m length 1inch paper core: Max. OD 67mm, 300m length				

## Connectivity

USB	USB version 2.0 (full speed) Type B				
USB host capability			Yes	Yes	Yes
Serial	Serial RS232C (DB9 male)			Serial RS232C (DB9 female)	
Wired LAN	10/100BASE-TX			10/100BASE-TX	
USB host port			Yes	Yes	Yes
Bluetooth	Version 4.2				
Bluetooth profile	SPP, OPP, HCRP Bluetooth Classic, GATT (Bluetooth Low Energy)				
Wireless LAN	802.11a/b/g/n				
Wireless LAN security	Authentic method (encryption scheme) Infrastructure mode- Open system (None/ WEP64/WEP128) Common key authentication (WEP) WPA/WPA2- PSK (TKIP+AES), EAP-FAST (TKIP/AES), PEAP (TKIP/AES), EAP-TLS (TKIP/AES), EAP-TTLS (TKIP/AES) Authentic method (encryption scheme) Wireless direct mode -WPA2-PSK (AES)				
MFI support	No	No	No	Yes	No
AirPrint	No	No	No	Yes	No
Wired LAN	No	Yes	Yes	Yes	Yes



TD-4410D	TD-4420DN	TD-4520DN	TD-4550DNWB	TD-4420TN	TD-4520TN
4 Inch					

## General

Control panel	3 button 3 LED	7 button 3 LED	1 button 1 LED with 3 colours
LCD type		Mono	

## Power

Adapter	AC adapter (100 - 240V 50/60Hz)	AC adapter Input: AC 100-240V, 2.0A, 50-60Hz Output: DC24V, 2.5A, 60W, LPS
---------	---------------------------------	--

## Software

Operating system support	Windows 7/8/8.1/10 Linux	Windows 7/8/8.1/10 Windows Server 2008/2008R2/2012/2012R2/2016 Linux	Windows 7/8/8.1/10, Windows Server 2008/2008R2/2012/2012R2/2016 OS X 10.10.x,10.11.x macOS 10.12.x,10.13.x,10.14.x Linux
Supported printer commands	P-touch Template, ESC/P, Raster, ZPL II emulation, CPCL emulation		FBPL-EZD (EPL,ZPL,ZPL2,DPL) emulation
Barcode symbologies	<p>Linear: CODE 39, ITF(-2/5), EAN-8(JAN8), EAN-13(JAN13), UPC-A, UPC-E, CODABAR (NW-7), CODE 128, GS1-128(UCC/EAN 128), GS1 Databar (Standard (Omnidirectional)/Truncated/Stacked/Stacked Omnidirectional/ Limited/ Expanded), CODE93, POSTNET, UPC/EAN EXTENSION, MSI, Intelligent Mail Barcode 2-dimensional: QR Code (model 1, model 2, micro QR), Maxicode, PDF417 (Standard, Truncate, MicroPDF417)</p> <p>Data Matrix (ECC200 Square, ECC200 Rectangular) Aztec</p>		<p>Linear: Code128UCC, Code128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code11, TELEPEN, TELEPENN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS</p> <p>2-dimensional: GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417</p>
Internal fonts	<p>ESC/P-&gt; Bitmap font: LetterGothicBold (16,24,32,48dot), Helsinki (16,24,32,48dot), Brussels (24,32,48dot), Brougham (24,32,48dot), San Diego (24,32,48dot), Gothic (16,24,32dot)</p> <p>Outline font: LetterGothicRegular, Helsinki, Brussels, Gothic (1 – 400dots) &lt;P-touch Template&gt;</p> <p>Outline font: LetterGothicRegular, Helsinki, Brussels, Gothic (1 – 400dots)</p> <p>Downloadable font support* via Font Manager software</p>		<p>8 alpha-numeric bitmap fonts for FBPL Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</p>

## Memory

RAM	256MB	64MB
Flash	64MB	128MB

## Environmental

Operating temperature	Operate: 5°C to 40°C	Operate: 5°C to 40°C
Operating humidity	20 - 85% (No condensation, Max wet bulb temperature: 27°C)	25 - 85% non-condensing
Storage temperature	-20°C to 60°C	-40°C to 60°C
Storage humidity	10 - 90% (No condensation)	10 - 90% non-condensing

## Weights & Dimensions

Dimensions (mm)	180(w) x 155(d) x 224(h)	204(w) x 178(d) x 280(h)
Weights	2.08kg	2.5kg

## Included Items

Supplied in box	AC adaptor & cord, USB cable, documentations	AC adaptor & cord, USB cable, documentations. Pair of 1" Ribbon spindles for 300M ribbon 1" ribbon paper core
-----------------	--	--

# brother

at your side

Contact:

**brother.co.nz**

**Brother International NZ Ltd.**  
27 Matarawa Place, Tauriko  
Tauranga 3171  
Tel: 07 543 5600

SOL-001-V2-1219