P-touch E550WVP

brother at your side

Industrial PC labelling machine

Create durable labels for electrical or datacom installations, via the easy-to-use built-in labelling functions, PC software or from your smartphone or tablet with the Brother cable labelling app.

- Large backlit graphic display
- Advanced cutter for easy-to-peel labels
- Includes 2 tape cassettes, AC adapter, lithium-ion battery, USB cable, hand strap and carry case
- Prints 6, 9, 12, 18 and 24mm labels

www.brother..co.nz

"Clear identification and safety are critical in my line of work, and being able to print durable labels from my PC or smartphone gives me total flexibility, whatever job I am on."

Mobile Cable Label Tool 08:52

240 VOLTS
ADD — Simple Label/ Heatshrink Tube

A-B01 — Faceplate

A-B01 — Cable Wrap

A-B01 — Cable Flag

01 : 02 : 03 : 04 — Patch Panel

1 2 / 7 8 — Punch Down Block

Saved Labels/Print Log

P-touch
E550WVP

P-touch E550WVP

Ensuring cables, conduits, switches and sockets are clearly identified with long lasting, durable labels is essential for electricians, datacom, telecom and security equipment installers. The Brother P-touch E550WVP creates labels that help address ANSI/EIA/TIA-606A/B, and that meet the UL-969 standards.

Prints labels 3.5 to 24mm in width

Print labels in various widths to suit any space

Large backlit graphic LCD

Easily view symbols and preview your label before printing

Sequential numbering

Print labels containing a sequence of numbers or letters

384 built-in symbols

Includes common electrical, datacom, AV, security and safety symbols

Automatic label cutter with easy peel

Keeps multiple labels in the correct order

Specialist label functions

Easily create general, faceplate, cable flag/wrap, patch panel and punch down block labels

Database search/merge/print

Upload data from your PC to print labels on-site

USB & Wi-Fi

Print from PC or mobile wirelessly

P-touch laminated labels – designed to last

Brother P-touch laminated TZe tapes are available in many different colours and sizes. The thermal transfer ink is sandwiched between two protective layers of PET (polyester film), protecting the text against the effects of liquids, abrasion, temperature, chemicals and sunlight. As the labels have been tested to the extreme, you can be confident of a professional quality label that has been designed to last.

P-touch LABELS TESTED TO THE EXTREME

| Laminated | Temperature Resistant | Water Resistant | Fade Resistant | Abrasion Resistant | Chemical Resistant | Easy Peel | Strong Adhesion |

Specialist tape cassettes

In addition to the extensive range of TZe tapes in various colours and sizes, specialist tapes for industrial use have been developed for specific labelling tasks.

Flexible-ID Tape
Use on: Curved surfaces or itself

- Wrapping/flagging individual wires
- Sharp bends
- Cylindrical surfaces

Strong Adhesive Tape
Use on: Uneven, rough and textured surfaces

- Painted metal
- Powder-coated surfaces
- Utility cabinets

Heat-shrink tube
Use on: Wires and cables

- Shrinks and grips cable when heat is applied
- Permanent
- Durable

Technical Specifications

Main features

Display type	16 chrs x 3 lines backlit graphic LCD with print preview
Interfaces	USB 2.0, Wi-Fi, Wireless Direct
Print speed	30mm / second (maximum)
Maximum tape width	24mm
Maximum print height	18mm
Cutter type	Automatic (Full & Half)
Battery type	BA-E001 Li-ion rechargeable battery (supplied) 6 x AA alkaline/rechargeable batteries (LR6/HR6 - not supplied)

Label creation

Dedicated labelling functions	General ¦ Faceplate ¦ Patch panel ¦ Punch block ¦ Cable wrap ¦ Cable flag ¦ Heat shrink tube Serialise (automatic number incrementation)
Fonts	14 fonts ¦ 10 styles ¦ 6 to 48 point size
Max. lines per label	7 (on 24mm width tape cassette)
Max. text blocks	99
Symbols	384
Frames	7
Barcodes	9 protocols
Automatic numbering	1-99
Copy printing	1-99
Vertical text printing	Yes
Rotated text printing	Rotate once ¦ Rotate and repeat

Memory

Maximum characters per label	1500
Label memory locations	99

PC software main features

Supported operating systems	Windows Vista®, Windows® 7, Windows® 8, Mac OS X 10.6 - 10.9
Cable labelling wizard	Yes
Font faces	All installed true-type fonts
Font styles	12
Image import	JPG, BMP, TIFF and other popular types
Screen capture	Yes
Frames	153
Barcodes	21 protocols including 1D/2D barcodes

Included items

In the box	PT-E550 labelling machine 12mm black on white Flexible ID tape (8m) Li-ion rechargeable battery AC adapter Label design software and printer driver CD-ROM USB cable, wrist strap and user guide

Supplies

Tape type ¦ Tape widths	TZe tape cassettes ¦ 3.5, 6, 9, 12, 18, 24mm HSe tube cassettes ¦ 5.8, 8.8, 11.7, 17.7, 23.6mm

Optional accessories

Batteries	BA-E001 Li-ion rechargeable battery AA alkaline/rechargeable batteries (LR6/HR6)
AC adapter	AD-E001 AC adapter

Weights & Dimensions

PT-E550WVP	126mm(w) x 250mm(h) x 94mm(d) ¦ 1.05kg

Contact:

brother
at your side

Brother Earth
Working with you for a better environment

HSe TUBE
5.8mm 8.8mm 11.7mm 17.7mm 23.6mm

TZe TAPE
3.5mm 6mm 9mm 12mm 18mm 24mm